

Technical data

For the complete range of loads/pressures, consult the technical catalogue.



TM1000 High Power

Size	Load-Index/ Speed Symbol	psi									
		6	9	12	14	17	20	23	26	30	35
IF 600/70R30 TL	159D	Up to 65 km/h (*)									
		Field Service (*)									
IF 650/60R34 TL	159D	Up to 65 km/h (*)									
		Field Service (*)									
IF 650/65R34 TL	161D	Up to 65 km/h (*)									
		Field Service (*)									
IF 710/60R34 TL	164D	Up to 65 km/h (*)									
		Field Service (*)									
IF 650/65R38 TL	169D	Up to 65 km/h (*)									
		Field Service (*)									
IF 710/60R38 TL	172D	Up to 65 km/h (*)									
		Field Service (*)									
IF 710/70R42 TL	179D	Up to 65 km/h (*)									
		Field Service (*)									
IF 710/75R42 TL	176D	Up to 65 km/h (*)									
		Field Service (*)									
IF 900/60R42 TL	180D	Up to 65 km/h (*)									
		Field Service (*)									
IF 710/65R46 TL	183D	Up to 65 km/h (*)									
		Field Service (*)									
IF 750/75R46 TL	186D	Up to 65 km/h (*)									
		Field Service (*)									
IF 900/65R46 TL	190D	Up to 65 km/h (*)									
		Field Service (*)									

TM900 High Power

Size	Load-Index/ Speed Symbol	psi									
		9	12	14	17	20	23	26	30	35	
600/70R28 TL	157D (154E)	Up to 65 km/h (*)									
		Field Service (*)									
600/70R30 TL	158D (155E)	Up to 65 km/h (*)									
		Field Service (*)									
710/60R30 TL	162D (159E)	Up to 65 km/h (*)									
		Field Service (*)									
600/70R34 TL	160D (157E)	Up to 65 km/h (*)									
		Field Service (*)									
650/60R34 TL	159D (156E)	Up to 65 km/h (*)									
		Field Service (*)									
710/60R34 TL	164D (161E)	Up to 65 km/h (*)									
		Field Service (*)									
650/75R38 TL	169D (166E)	Up to 65 km/h (*)									
		Field Service (*)									
650/85R38 TL	173D (170E)	Up to 65 km/h (*)									
		Field Service (*)									
800/70R38 TL	178D (175E)	Up to 65 km/h (*)									
		Field Service (*)									
900/60R38 TL	178D (175E)	Up to 65 km/h (*)									
		Field Service (*)									
710/70R42 TL	173D (170E)	Up to 65 km/h (*)									
		Field Service (*)									
710/70R42 TL (for harvesting applications)	179A8	Up to 65 km/h (*)									
		Field Service (*)									
710/75R42 TL	175D (172E)	Up to 65 km/h (*)									
		Field Service (*)									
900/60R42 TL	180D (177E)	Up to 65 km/h (*)									
		Field Service (*)									

TM1060

Size	Load-Index/ Speed Symbol	psi									
		9	12	14	17	20	23	26	30	35	
VF 520/60R28	149D	Up to 65 km/h (*)									
		Field Service (*)									
VF 600/60R28	157D	Up to 65 km/h (*)									
		Field Service (*)									
VF 600/60R30	158D	Up to 65 km/h (*)									
		Field Service (*)									
VF 650/60R38	166D	Up to 65 km/h (*)									
		Field Service (*)									
VF 710/60R38	171D	Up to 65 km/h (*)									
		Field Service (*)									
VF 710/60R42	173D	Up to 65 km/h (*)									
		Field Service (*)									

TM800

Size	Load-Index/ Speed Symbol	psi									
		9	12	14	17	20	23	26	30	35	
320/65R18	109A8 (109B)	Up to 65 km/h (*)									
		Field Service (*)									
340/65R18	113A8 (113B)	Up to 65 km/h (*)									
		Field Service (*)									
440/65R24 TL	128D	Up to 65 km/h (*)									
		Field Service (*)									
480/65R24 TL	133D	Up to 65 km/h (*)									
		Field Service (*)									
540/65R24 TL	140D	Up to 65 km/h (*)									
		Field Service (*)									
540/65R24 TL (for harvesting applications)	146A8	Up to 65 km/h (*)									
		Field Service (*)									
540/65R26 TL	141D	Up to 65 km/h (*)									
		Field Service (*)									
440/65R28 TL	131D	Up to 65 km/h (*)									
		Field Service (*)									
480/65R28 TL	136D	Up to 65 km/h (*)									
		Field Service (*)									
540/65R28 TL	142D	Up to 65 km/h (*)									
		Field Service (*)									
600/65R28 TL	147D	Up to 65 km/h (*)									
		Field Service (*)									
540/65R30 TL	143D	Up to 65 km/h (*)									
		Field Service (*)									
540/65R34 TL	145D	Up to 65 km/h (*)									
		Field Service (*)									
600/65R34 TL	151D	Up to 65 km/h (*)									
		Field Service (*)									
540/65R38 TL	147D	Up to 65 km/h (*)									
		Field Service (*)									
600/65R38 TL	153D	Up to 65 km/h (*)									
		Field Service (*)									
650/65R38 TL	157D	Up to 65 km/h (*)									
		Field Service (*)									
710/70R38 TL	163D	Up to 65 km/h (*)									
		Field Service (*)									
710/70R38 TL (for sugarcane applications)	166D	Up to 65 km/h (*)									
		Field Service (*)									
710/70R38 TL (forage)	175D	Up to 65 km/h (*)									
		Field Service (*)									
600/65R42 TL	154D	Up to 65 km/h (*)									
		Field Service (*)									
650/65R42 TL	158D	Up to 65 km/h (*)									
		Field Service (*)									

TM800 High Speed

Size	Load-Index/ Speed Symbol	psi									
		9	12	14	17	23	26	29	32	35	
540/65R28 TL	149D (146E)	Up to 40 km/h (*)									
		Field Service (*)									
600/65R28 TL	154D (151E)	Up to 40 km/h (*)									
		Field Service (*)									
540/65R30 TL	150D (147E)	Up to 40 km/h (*)									
		Field Service (*)									
540/65R34 TL	152D (149E)	Up to 40 km/h (*)									
		Field Service (*)									
600/65R34 TL	157D (154E)	Up to 40 km/h (*)									
		Field Service (*)									
540/65R38 TL	153D (150E)	Up to 40 km/h (*)									
		Field Service (*)									
650/65R38 TL	163D (159E)	Up to 40 km/h (*)									
		Field Service (*)									
710/70R38 TL	171D (168E)	Up to 40 km/h (*)									
		Field Service (*)									
300/70R20 TL	110A8 (110B)	Up to 40 km/h (*)									
		Field Service (*)									
320/70R20 TL	113A8 (113B)	Up to 40 km/h (*)									
		Field Service (*)									
360/70R20 TL	120A8 (120B)	Up to 40 km/h (*)									
		Field Service (*)									
380/70R20 TL	122A8 (122B)	Up to 40 km/h (*)									
		Field Service (*)									
320/70R24 TL	116A8 (116B)	Up to 40 km/h (*)									
		Field Service (*)									
360/70R24 TL	122A8 (122B)	Up to 40 km/h (*)									
		Field Service (*)									
380/70R24 TL	125A8 (125B)	Up to 40 km/h (*)									
		Field Service (*)									
420/70R24 TL	130A8 (130B)	Up to 40 km/h (*)									
		Field Service (*)									
480/70R24 TL	138A8 (138B)	Up to 40 km/h (*)									
		Field Service (*)									
480/70R26 TL	139A8 (139B)	Up to 40 km/h (*)									
		Field Service (*)									
320/70R28 TL	119A8 (119B)	Up to 40 km/h (*)									
		Field Service (*)									
360/70R28 TL	125A8 (125B)	Up to 40 km/h (*)									
		Field Service (*)									
380/70R28 TL	127A8 (127B)	Up to 40 km/h (*)									
		Field Service (*)									
420/70R28 TL	133D	Up to 40 km/h (*)									
		Field Service (*)									
480/70R28 TL	140D	Up to 40 km/h (*)									
		Field Service (*)									
480/70R28 TL	145D (148A8)	Up to 40 km/h (*)									
		Field Service (*)									
420/70R30 TL	134A8 (134B)	Up to 40 km/h (*)									
		Field Service (*)									
480/70R30 TL	141D	Up to 40 km/h (*)									
		Field Service (*)									
520/70R30 TL	145A8 (145B)	Up to 40 km/h (*)									
		Field Service (*)									
480/70R34 TL	143A8 (143B)	Up to 40 km/h (*)									
		Field Service (*)									
480/70R34 TL	155A8 (155B)	Up to 40 km/h (*)									
		Field Service (*)									
520/70R34 TL	148A8 (148B)	Up to 40 km/h (*)									
		Field Service (*)									
480/70R38 TL	145A8 (145B)	Up to 40 km/h (*)									
		Field Service (*)									
580/70R38 TL	155D	Up to 40 km/h (*)									
		Field Service (*)									
580/70R42 TL	158D	Up to 40 km/h (*)									
		Field Service (*)									
620/70R42 TL	166D	Up to 40 km/h (*)									
		Field Service (*)									

TM700 ProgressiveTraction™

Size	Load-Index/ Speed Symbol	psi									
		9	12	14	17	20	23	26	30	35	
380/70R28	127D	Up to 40 km/h (*)									
		Field Service (*)									
420/70R28	133D	Up to 40 km/h (*)									
		Field Service (*)									
480/70R28	140D	Up to 40 km/h (*)									
		Field Service (*)									
480/70R38	141D	Up to 40 km/h (*)									
		Field Service (*)									
480/70R38	145D	Up to 40 km/h (*)									
		Field Service (*)									
520/70R38	150D	Up to 40 km/h (*)									
		Field Service (*)									
580/70R38	155D	Up to 40 km/h (*)									
		Field Service (*)									
580/70R42	158D	Up to 40 km/h (*)									
		Field Service (*)									
620/70R42	166D	Up to 40 km/h (*)									
		Field Service (*)									

TM700 High Speed

Size	Load-Index/ Speed Symbol	psi									
		9	12	14	17	23	26	29	32	35	
480/70R30 TL	147D (144E)	Up to 40 km/h (*)									
		Field Service (*)									
520/70R30 TL	151D (148E)	Up to 40 km/h (*)									
		Field Service (*)									
240/70R16 TL	104A8 (104B)	Up to 40 km/h (*)									
		Field Service (*)									
260/70R16 TL	109A8 (109B)	Up to 40 km/h (*)									
		Field Service (*)									
280/70R16 TL	112A8 (112B)	Up to 40 km/h (*)									
		Field Service (*)									
280/70R18 TL	114A8 (114B)	Up to 40 km/h (*)									
		Field Service (*)									
280/70R20 TL	116A8 (116B)	Up to 40 km/h (*)									
		Field Service (*)									

TM600

Size	Load-Index/ Speed Symbol	psi									
		9	12	14	17	23	26	29	35	43	
210/95R16 TL (7.50R16)	106A8 (106B)	Up to 40 km/h (*)									
		Field Service (*)									
210/95R18 TL (7.50R18)	108A8 (108B)	Up to 40 km/h (*)									
		Field Service (*)									
280/85R20 TL (11.2R20)	112A8 (109B)	Up to 40 km/h (*)									
		Field Service (*)									
320/85R20 TL (12.4R20)	119A8 (116B)	Up to 40 km/h (*)									
		Field Service (*)									
280/85R24 TL (11.2R24)	115A8 (112B)	Up to 40 km/h (*)									
		Field Service (*)									
320/85R24 TL (12.4R24)	122A8 (119B)	Up to 40 km/h (*)									
		Field Service (*)									
340/85R24 TL (13.6R24)	125A8 (122B)	Up to 40 km/h (*)									
		Field Service (*)									
380/85R24 TL (14.9R24)	131A8 (128B)	Up to 40 km/h (*)									
		Field Service (*)									
420/85R24 TL (16.9R24)	137A8 (134B)	Up to 40 km/h (*)									
		Field Service (*)									
280/85R28 TL (11.2R28)	118A8 (115B)	Up to 40 km/h (*)									
		Field Service (*)									
320/85R28 TL (12.4R28)	124A8 (121B)	Up to 40 km/h (*)									
		Field Service (*)									
270/85R28 TL (12.4R28)	127A8 (124B)	Up to 40 km/h (*)									
		Field Service (*)									
380/85R28 TL (14.9R28)	133A8 (130B)	Up to 40 km/h (*)									
		Field Service (*)									
420/85R28 TL (16.9R28)	139A8 (136B)	Up to 40 km/h (*)									
		Field Service (*)									
380/85R30 TL (14.9R30)	135A8 (132B)	Up to 40 km/h (*)									
		Field Service (*)									
420/85R30 TL (16.9R30)	140A8 (137B)	Up to 40 km/h (*)									
		Field Service (*)									

TM500

Size	Load-Index/ Speed Symbol	psi									
		9	12	14	17	23	26	29	35	43	
420/90R30 TL (16.9R34)	147A8 (147B)	Up to 40 km/h (*)									
		Field Service (*)									
460/85R30 TL (18.4R30)	145A8 (142B)	Up to 40 km/h (*)									
		Field Service (*)									
380/85R34 TL (14.9R34)	137A8 (137B)	Up to 40 km/h (*)									
		Field Service (*)									
420/85R34 TL (16.9R34)	142A8 (139B)	Up to 40 km/h (*)									
		Field Service (*)									
420/85R34 TL (16.9R34)	147A8 (147B)	Up to 40 km/h (*)									
		Field Service (*)									
460/85R34 TL (18.4R34)	147A8 (144B)	Up to 40 km/h (*)									
		Field Service (*)									
340/85R38 TL (13.6R38)	133A8 (130B)	Up to 40 km/h (*)									
		Field Service (*)									

TM150

Size	Load-Index/ Speed Symbol	psi									
		9	12	14	17	23	26	29	35	43	
VF 380/90R46	173D	Up to 65 km/h (*)									
		Field Service (*)									
VF 380/105R46	178D	Up to 65 km/h (*)									
		Field Service (*)									
VF 380/105R50	179D	Up to 65 km/h (*)									
		Field Service (*)									
480/80R46 TL (18.4R46)	158A8 (158B)	Up to 40 km/h (*)									
		Field Service (*)									
520/85R46 TL (20.8R46)	158A8 (158B)	Up to 40 km/h (*)									
		Field Service (*)									
480/80R50 TL	159D	Up to 40 km/h (*)									
		Field Service (*)									

TM100

Size	Load-Index/ Speed Symbol	psi									
		14	17	20	23	29	35	41	46	52	58
270/95R32 TL	128A8 (128B)	Up to 40 km/h (*)									
		Field Service (*)									
270/95R32 TL	136A8 (136B)	Up to 40 km/h (*)									
		Field Service (*)									
230/95R36 TL	130A8 (130B)	Up to 40 km/h (*)									
		Field Service (*)									
270/95R38 TL	140A8 (140B)	Up to 40 km/h (*)									
		Field Service (*)									
210/95R44 TL	120A8 (120B)	Up to 40 km/h (*)									
		Field Service (*)									
230/95R44 TL	134A8 (134B)	Up to 40 km/h (*)									
		Field Service (*)									
300/95R46 TL	148A8 (148B)	Up to 40 km/h (*)									
		Field Service (*)									
230/95R48 TL	136A8 (136B)	Up to 40 km/h (*)									
		Field Service (*)									
2											